

PINEBERRY CARTONTRAC FC FOR SERIALIZATION

Product is placed on the Pineberry HSF 12 Friction Feeder and is dispensed as a single product from the product stack. The product is transported through the feeder exit, and will print variable data onto the product. As products exit the feeder the camera system will verify the data and then exits onto the integrated CartonTrac FC—Flat Carton Serialization Solution.

Features:

- HSF 12 Friction Feeder
- Camera Verification System
- In-line Printing
- Shingling Exit Conveyor
- Prints All Barcodes

Material Sizes

- Up to 12" wide product
- *Can engineer for wider formats

Material Thickness

- .003" up to .031"
- *Various sizes available

Applications:

- Serialization
- UDI Codes
- Date/Lot Coding
- Barcode Verification

Speeds

- Up to 250 per minute

Power Requirements

- 110V or 220V



Options:

- PLC Interface
- Transfers from Conveyor to Conveyor
- Sorting and Batching of Product
- Software Integration
- Laser Print Integration
- Multiple Vendors Inkjet Print Integration



12345678

Code 39



Micro PDF



QR Code



12345678

Code 128

All barcodes above can be printed/read/verified on the Pineberry CartonTrac FC.



PINEBERRY CARTONTRAC FC FOR SERIALIZATION

